

#### LOAD LIMITS

- La portata massima è di **680Kg (1500 lbs)** con angolo settato a 0°.
- La KPTAX800L può sospendere fino ad un massimo di: **12 AX800A**
- L'utilizzo in appoggio permette di montare massimo **4 AX800A**.
- Maximum capacity is **680Kg (1500 lbs)** with the angle set at 0°.
- KPTAX800L flying bar can suspend up to: **12 AX800A**
- In a stack configuration you can stack up to **4 AX800A**.




#### CONDITIONS OF USE



Proel declina ogni responsabilità per danni a terzi causati da mancata manutenzione, manomissioni, uso improprio o installazione senza rispetto delle norme di sicurezza standard. Proel raccomanda che i diffusori siano sospesi tenendo conto di tutte le attuali norme nazionali, federali, statali e locali. Il prodotto deve essere installato da personale qualificato. Contattare il produttore per qualsiasi informazione.

Proel do not accept any liability for damage caused to third parties due to improper installation, lack of maintenance, tampering or improper use of this product, including disregard of acceptable and applicable safety standards.

Proel strongly recommends that this loudspeaker cabinet be suspended taking into consideration all current National, Federal, State and Local regulations. The product must be installed by qualified personnel. Please contact the manufacturer for further information.



**CUSTOMER** .....

**BATCH NO.** .....